

IMPROVING DEVELOPMENT EFFICIENCY OF
ABNORMALLY LOW-PRESSURE, SMALL-RESERVE
GAS-CONDENSATE FIELDS

Ermatov Navruz Xushmuradovich

navruzermatov626@gmail.com

Boyqobilova Mahliyo Mahmudovna

boyqobilovamahliyo52@gmail.com

Akhatova Guliza Anvar qizi

gaxatova045@mail.ru

Bozorov Ulugbek Suyun ogli

ulugbek.bozorov.1991@gmail.com

Karshi, Uzbekistan

ABSTRACT. *Abnormally low-pressure gas-condensate fields with small reserves often suffer from rapid deliverability loss and declining liquid hydrocarbon recovery once pressure falls below dew-point, triggering retrograde condensate dropout and near-wellbore condensate banking. This paper synthesizes global research and field-proven concepts into an integrated framework linking abnormal-pressure characterization, phase-behavior risk, near-well deliverability evaluation, and concept selection under small-reserve economic constraints. The workflow screens and ranks depletion with surface compression, partial gas cycling, and facility-driven options, and is implementable with standard PVT, well-test, and compositional simulation tools.*

KEYWORDS: *abnormally low reservoir pressure; gas-condensate; retrograde condensation; condensate banking; gas cycling; compression; marginal field development; integrated workflow.*

NOMENCLATURE

P_{dew} – dew-point pressure; P_r – reservoir pressure; BHP – bottomhole pressure; CGR – condensate-gas ratio; k, h, φ – permeability, thickness, porosity; $\frac{k_v}{k_h}$ – vertical-to-horizontal permeability ratio; K_a – abnormal pressure coefficient (normalized pressure indicator; regional definitions may differ).

1. INTRODUCTION

Gas-condensate reservoirs exhibit a distinctive depletion behavior: once near-wellbore flowing pressure drops below the dew-point pressure (P_{dew}), liquid condensate forms in situ and can accumulate around the wellbore. The resulting condensate banking reduces gas relative permeability and causes a marked drop in well deliverability and liquid recovery.

In abnormally low-pressure systems, the operating window is narrower: smaller pressure margins increase sensitivity to drawdown, stress-dependent permeability, and facility back-pressure, accelerating below-dew-point flow and intensifying condensate banking.

For small-reserve fields, the challenge is dual: mitigate condensate-banking-driven losses while choosing development concepts that remain economically viable (limited wells, lean facilities, tie-back constraints, and staged investments). This paper offers a structured framework integrating reservoir physics and development-concept selection.

2. LITERATURE BACKGROUND AND KEY LEARNINGS

2.1. Condensate banking and near-wellbore deliverability

Productivity loss below P_{dew} is governed by condensate-bank growth, gas/condensate relative permeability behavior, capillary and inertial effects, and—where applicable—velocity-dependent non-Darcy flow in the near-well region. These mechanisms motivate fine-grid compositional modeling or specialized well models for reliable deliverability forecasts.

2.2. Pressure management: depletion, compression, and gas cycling

Gas cycling (dry-gas injection) can increase condensate recovery by maintaining pressure closer to P_{dew} and re-vaporizing part of dropped-out liquids. Benefit depends on cycling start timing, injection–production pattern design, and the trade-off between incremental recovery and CAPEX/OPEX—especially critical for small reserves.

2.3. Abnormally low-pressure reservoirs: why they behave tighter

Abnormally low-pressure conditions are often described using normalized pressure indicators supported by pressure surveys and well tests. Such reservoirs can show elevated sensitivity to compressibility assumptions and pressure-dependent flow capacity, which should be reflected in material-balance and simulation workflows.

2.4. Small-reserve development concepts


Marginal-field development literature emphasizes simplified facility configurations (no treating / partial treating / full treating), flow assurance, and tie-back constraints as key determinants of commercial viability. This logic is directly applicable to small-reserve gas-condensate developments.

3. PROPOSED INTEGRATED FRAMEWORK

3.1. Framework overview

A six-module workflow couples reservoir physics with development-concept decisions. The workflow quantifies retrograde risk, condensate-banking severity, and deliverability impact; screens feasible concepts under small-reserve constraints; and defines an operating envelope with surveillance triggers enabling staged upgrades.

Figure 1. Integrated workflow (screening → modeling → decision)



(depletion+compression vs partial cycling vs staged facilities)

|
v

Optimization & Surveillance

(operating envelope, cycling trigger, KPIs, history match updates)

3.2. Module 1 – Data preparation and constraints mapping

Minimum dataset:

- PVT report or EOS-tuning inputs (CGR vs pressure, P_{dew} ; separator tests if available).
- Well tests and production logs, including BHP/THP history where possible.
- Reservoir properties: k , h , ϕ , net-to-gross, heterogeneity indicators, kv/kh, initial pressure, and pressure survey quality.
- Facility constraints: maximum compression ratio, minimum suction pressure, separator pressures, tie-back line pressure drops, hydrate-control approach.

Outputs: a constraint map defining feasible BHP window versus rate, and an estimate of when facility constraints force BHP below P_{dew} .

3.3. Module 2 – Abnormally low-pressure characterization and stress sensitivity

Evaluate abnormality using a normalized pressure indicator (e.g., K_a) together with pressure gradients and well-test evidence. Treat sensitivity to compressibility assumptions and potential stress-dependent permeability explicitly, at least as uncertainty bands when laboratory data are unavailable.

Recommended checks:

- Sensitivity of gas-in-place and recovery forecasts to effective compressibility assumptions and water saturation.
- Evidence of pressure-dependent flow capacity (stress sensitivity) inferred from tests or production behavior.
- Ranking of wells/areas by pressure fragility (low / medium / high) to guide drawdown policy.

3.4. Module 3 – Phase behavior and retrograde exposure index

A practical screening index is:

$$REI = \frac{(P_{dew} - P_{wf})}{P_{dew}}$$

where P_{wf} is a representative near-wellbore flowing pressure (from tests or nodal analysis). Higher REI implies higher condensate-banking risk.

3.5. Module 4 – Near-well deliverability and condensate banking severity

Two implementation levels are recommended:

Level A (fast screening): Apply semi-analytical adjustments (e.g., condensate blockage skin concepts) based on tests and trends when data are limited.

Level B (engineering-grade): Perform fine-grid compositional simulation near the wellbore (or use a coupled well model) and calibrate to test/production history.

Actionable outputs:

- Banking onset threshold (BHP or P_{wf}) at which productivity decline accelerates.
- Deliverability penalty curve: $\frac{J}{J_0}$ versus REI.

– Ranking of wells by banking controllability (drawdown control vs need for cycling/recompletion).

3.6. Module 5 – Concept screening for small reserves

Balance reservoir effectiveness with small-reserve viability. Typical concepts include depletion with staged surface compression, partial cycling (targeted dry-gas injection), full cycling (usually economic only when infrastructure exists), and facility-driven options such as no/partial/full treating and tie-back configuration changes.

3.7. Module 6 – Optimization rules and cycling trigger logic

Use staged triggers to avoid starting cycling too late or designing patterns that lead to early breakthrough. Primary triggers may include: (i) reservoir pressure approaching P_{dew} in the drainage region, (ii) accelerated PI decline consistent with below-dew-point flow, and (iii) facility back-pressure forcing BHP below the banking-onset threshold. Optimization levers include drawdown (BHP constraint), compression staging, cycling start timing relative to P_{dew} , and injector placement to manage breakthrough risk.

Table 1. Factors controlling liquid hydrocarbon recovery in abnormally low-pressure gas-condensate fields

Group	Factor	Typical impact	Notes
Geo-physical	k, h	Higher k or $h \rightarrow$ higher deliverability; banking delayed	Baseline potential

FRONTIERS OF KNOWLEDGE AND INTERDISCIPLINARY DISCOVERY
international scientific conference

Group	Factor	Typical impact	Notes
Geo-physical	Heterogeneity, $\frac{k_v}{k_h}$	Higher contrast → localized banking risk increases	May need zonal strategy
Geo-physical	Stress sensitivity	Pressure decline → flow capacity decreases	Critical at low pressure
Fluid/PVT	P_{dew} , CGR	Higher retrograde tendency → banking risk increases	EOS tuning important
Operations	BHP drawdown	Higher drawdown → earlier below- dew-point flow	Primary controllable lever
Operations	Compression & separator pressure	Better pressure management → lower retrograde exposure	Often high ROI
Pressure management	Gas cycling	Can increase condensate recovery if timely	Pattern & economics govern

Table 2. Decision matrix for concept selection in small-reserve, abnormally low-pressure gas-condensate fields

Screening condition	Preferred concept	Why	Watch-outs
Limited CAPEX; tie-back available; strong back-pressure constraints	Depletion + staged compression + separator optimization	Fast implementation; preserves BHP margin	May still enter below-dew-point if reservoir weak
P_r near P_{dew} ; high CGR; banking-driven PI loss observed	Partial cycling (staged/targeted)	Pressure support plus re-vaporization potential	Pattern design and breakthrough risk
Existing injection/compression infrastructure present	Full cycling	Maximum control over retrograde exposure	Economic risk for small reserves
Remote development with treating/flow assurance limitations	Facility configuration optimization (no/partial/full treating)	Keeps project feasible under constraints	Hydrate management and flow assurance critical

4. DISCUSSION

To strengthen publishability, complement the workflow with either (i) a compact case study (field or calibrated synthetic), (ii) a sensitivity study on cycling start timing relative to P_{dew} and its impact on condensate recovery and

plateau duration, or (iii) a simple economics layer (e.g., NPV ranking) consistent with marginal-field decision-making.

5. CONCLUSIONS

1. In abnormally low-pressure gas-condensate fields, liquid recovery losses are primarily governed by retrograde exposure and near-wellbore condensate banking, which degrades deliverability below P_{dew} .

2. Small-reserve constraints require coupling physics-based banking evaluation with concept screening (compression versus partial cycling versus facility simplification).

3. Gas cycling can improve condensate recovery, but benefits depend on timing, pattern design, and economic feasibility; a staged trigger approach is recommended.

4. The proposed workflow is implementable with standard PVT/EOS, nodal analysis, and compositional simulation tools, and should be iteratively updated via surveillance and history matching.

REFERENCES

- [1] O. Fevang and C. H. Whitson, "Gas Condensate Relative Permeability for Well Calculations," SPE Paper 56476.
- [2] R. R. Lal, *Well Testing in Gas-Condensate Reservoirs*. Stanford Petroleum Engineering Report, 2003.
- [3] J. F. App, "Relative Permeability Estimation for Rich Gas-Condensate Systems from Well Test Data," *Transport in Porous Media*, 2005.
- [4] O. R. Butterfield, "Reservoir Analysis and Recovery Prediction for Cycling Gas-Condensate Reservoirs," SPE Paper 1217-MS, 1965.
- [5] *Development of Marginal Fields for Offshore Nova Scotia – Phase 2 of 2*, Rep. TR-10-15, 2010.

- [6] G. A. Axatova, Sh. Sh. Samatov, and G. Ch. Jo'rayeva, "Karbonat kollektorlarda kislotali ishlov berish samaradorligini quduq atrofi zonasining geologik tuzilishi bilan uyg'un modellashtirish [Integrated modeling of carbonate acidizing efficiency with near-wellbore geological structure]," *Ta'lim Innovatsiyasi va Integratsiyasi*, vol. 54, no. 1, pp. 217–222, 2025.
- [7] N. X. Ermatov, Sh. Sh. Samatov, M. M. Boyqobilova, and G. A. Axatova, "Karbonat kollektorlarga kislotali ishlov berishni modellashtirish (Matonat va G'arbiy Kruk konlari misolida) [Modeling acid stimulation in carbonate reservoirs: Matonat and G'arbiy Kruk fields]," *Innovatsion texnologiyalar*, no. 3(59), pp. 7–15, 2025.
- [8] A. I. Kornev, *Influence of Abnormal Pressure Coefficient on Field Development (Regional Classification and Applications)*. Tomsk, 2021.
- [9] M. Jamiolahmady *et al.*, "A generalized correlation for predicting gas–condensate relative permeability," *Journal of Petroleum Science and Engineering*, 2009.
- [10] T. V. Tran *et al.*, "Production Performance of Gas-Condensate Reservoirs: Compositional Numerical Model," SPE Paper 177445-MS, 2015.
- [11] M. Mahdaviara *et al.*, "Modeling relative permeability of gas-condensate reservoirs," 2020.
- [12] O. Udovchenko, J. Blicharski, and L. Matiishyn, "A Case Study of Gas-Condensate Reservoir Performance with Gas Cycling," *Archives of Mining Sciences*, 2024.